



NOTES:

2A  $\triangle$

- Rating: 300V  $\triangle$ (IEC 450V)  
PITCH: 3.50mm
- Insulation Withstands Voltage:  
AC 4000V/MIN
- Insulation Resistance:  
500M $\Omega$  or more at DC500V
- Using Temperature Range:  
-40°C~+105°C
- Suitable Electric Wire: 20~16 AWG

6. Undimensioned Tolerances:

$\pm$	$\sim$	$\square$	0.05/10
$\perp$	$\parallel$	$\equiv$	0.2/10
UNDIMENSIONS			0.05/10
TOLERANCES			$\pm 0.3$

ITEM	NAME OF PART	ND. OF PART	QTY	MATERIAL	NOTES
5	CLAMP	0136B00400	(P-1)/2 P/2	BRONZE	P P
4	COVER	0136A3XX00	1	PA66	GREY
3	LEVER	0136A5XX00	P	PA66	GREY
2	CLAMP	0136B00300	(P+1)/2 P/2	BRONZE	P P
1	HOUSING	0136A4XX00	P	PA66	GREY

REV.	CONTENT	CHK.	DATE
2	安插變更	H J	06.09.06

APP.	DATE	SCALE	SHEET/OF	NAME
		5:1 ( : )	1 / 2	0136-20XX

DINKLE ENTERPRISE CO.,LTD DWG NO. SP-02-013620XX