



**NOTES:**

1. Rating: 300V 10A (IEC 380V 16A)  
PITCH: 7.62mm
2. Insulation Withstands Voltage:  
AC 1500 V/MIN
3. Insulation Resistance:  
500MΩ or more at DC500V
4. Using Temperature Range:  
-40°C~+105°C
5. Suitable Electric Wire: AWG 22~14 (IEC 1.5mm<sup>2</sup>)
6. Undimensioned Tolerances:

—	∩	∇	0.05/10
⊥	//	≡	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONED TOLERANCES			±0.3

6	MID COVER	0018A00300	P-1	PA66(V0)	GREEN
5	END COVER	0018A00400	1	PA66(V0)	GREEN
4	LEVER	0018A10100 <del>0018A1XX00</del>	P	PA66(V2)	ORANGE
3	CLAMPING	0018B00300	P	STAINLESS STEEL	
2	SOLDER PIN	0018B00100	P	COPPER	Tin Plated
1	HOUSING	0018A00100	P	PA66(V0)	GREEN
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES

△4	工程變更	YFY	03.03.13	DWG.	蔣雪嬌	DATE	99,01,29	UNITS	MM	SHEET/OF	1/1
△3	工程變更	YFY	02.12.04	CHK.		DATE		SCALE	4:1 ( : )	⊕ ⊞	
△2	工程變更	XJIANG	01.04.16	APP.		DATE		NAME <b>142V-□□P3</b>			
△1	設計變更, 重新發行	蔣雪嬌	99,01,29	<b>DINKLE</b> ENTERPRISE CO.,LTD							
REV.	CONTENT	CHK.	DATE								