



- NOTES:
1. Rating: 300V 10A (IEC ~~250V 10A~~ 450V 24A) PITCH: 5.00mm
 2. Insulation Withstands Voltage: AC 1500 V/MIN
 3. Insulation Resistance: 500MΩ or more at DC500V
 4. Using Temperature Range: -40°C~+105°C (IEC 0.5~2.5mm²)
 5. Suitable Electric Wire: 20~14AWG (IEC 1.5~2.5mm²)
 6. Undimensioned Tolerances:

—	∩	∇	0.05/10
∩	∩	∇	0.2/10
PICH ARRAY	≡	∇	0.05/10
UNDIMENSIONS			±0.3
TOLERANCES			

△	工程變更	H J	06.06.14	△	1	HOUSING	0056ADXX00	P	PA66(V)	DP882 M001
△	工程變更 (2005.04改裝)	HQH	06.01.06	△	2	CLAMP	0056B00300	P	STEEL	
△	工程變更	YJ	05.05.16		3	SOLDER PIN	0056B00200	P	COPPER	
△	工程變更 光之塵	梁紅英	01.01.11	APP.	4	END COVER	0056A4XX00	1	PA66(V)	DP882 M001
△	工程變更	LHY	00.12.11		5	LEVER	0056A5XX00	P	POM	WHITE
△	CONTENT	CHK.	DATE							

ITEM	NAME OF PART	NO. OF PART	QTY	MATERIAL	NOTES
DWG.	DATE	DATE	UNITS	M/M	SHEET/OF
DATE	DATE	DATE	SCALE	5:1 (:)	1 / 2
APP.	DATE		NAME	144RA-□□P	
DINKLE ENTERPRISE CO., LTD					
DWG NO. SP-02-144RAP00					