



DOTS SIZE  
(FOR REFERENCE ONLY)

B/L CONNECTOR:  
JST 3HR-03VS-1  
OR EQUIVALENT

DISPLAY TYPE	5.7" TFT, TRANSMISSIVE, 262K COLOR	
DISPLAY RESOLUTION	320 X (RGB) X 240 DOTS	
VIEWING DIRECTION	50/40/60/60 (U/D/L/R)	
LOGIC VOLTAGE	3.3 V	
OPERATING TEMPERATURE	-20°C TO +70°C	
STORAGE TEMPERATURE	-30°C TO +80°C	
BACKLIGHT	TYPE	CCFL
	COLOR	WHITE
	WAVELENGTH	TBD
	DRIVING VOLTAGE	TBD
	LUMINANCE(cd/m <sup>2</sup> )	MIN. TBD
	(ON THIS BACKLIGHT	TYP. TBD
	SURFACE)	MAX. TBD
REMARK	ANTI-GLARE WIDE VIEWING FILM	

CNI PINS ASSIGNMENT:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
GND	CK	HSY	VSY	GND	R0	R1	R2	R3	R4	R5	GND	G0	G1	G2
16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
G3	G4	G5	GND	B0	B1	B2	B3	B4	B5	GND	ENAB	VCC	VCC	R/L
												U/D	V/Q	GND

- NOTES:
1. "◇" SPECIAL CHARACTERISTIC
  2. "+" SAFETY CHARACTERISTIC
  3. "▽" REFERENCE ONLY
  4. "C" CRITICAL DIMENSION