

DETAIL A


DISPLAY TYPE	2.9" TFT, +VE, TRANSMISSIVE	
DISPLAY RESOLUTION	26K COLORS	
VIEWING ANGLE	176 X ROB X 220 DOTS	
MUX RATIO AND BIAS RATIO	6 O' CLOCK	
LCD CONTROLLER/DRIVER	1/230 DUTY	
LOGIC VOLTAGE	HX8309A	
OPERATION TEMPERATURE	3.0V	
STORAGE TEMPERATURE	-20°C to +70°C	
BACKLIGHT	-30°C to +80°C	
	TYPE	
	LED02 (3 DIES)	
	COLOR	
	WHITE	
DRIVING VOLTAGE	TBD	
DRIVING CURRENT	45mA	
LUMINANCE (cd/m ²)	MIN	2300
(ON THE BACKLIGHT SURFACE)	TYP	2800
	MAX	-

REMARK: SUPER WIDE VIEWING FILM

SECTION B-B

PIN ASSIGNMENT

1	2	3	4	5	6	7	8	9	10	11	12	13
IM0	IM1	IM3	RESET	DB17	DB16	DB15	DB14	DB13	DB12	DB11	DB10	DB9
14	15	16	17	18	19	20	21	22	23	24	25	26
DB8	DB7	DB6	DB5	DB4	DB3	DB2	DB1	DB0	RD	WR	RS	CS
27	28	29	30									
VCC	VCI	GND	NC									



- NOTES:**
- ◇ : SPECIAL CHARACTERISTIC
 - + : SAFETY CHARACTERISTIC
 - ▽ : CRITICAL DIMENSION
 - (.) : REFERENCE DIMENSION