



DISPLAY TYPE	TFT, -VE, TRANSMISSIVE 262K COLOR	
DISPLAY RESOLUTION	240XRGBX320 DOTS	
VIEWING ANGLE	12.0° CLOCK	
MUX RATIO	1/250 DUTY	
LCD CONTROLLER / DRIVER	HX332A	
LOGIC VOLTAGE	3.3V(TYP)	
OPERATING TEMPERATURE	-20°C ~ 70°C	
STORAGE TEMPERATURE	-30°C ~ 80°C	
BACKLIGHT	TYPE	LED
	COLOR	WHITE
	WAVELENGTH	-
	DRIVING VOLTAGE	~1.2V @ 20MA
LUMINANCE (cd/m²)	Min.	3000
	Typ.	3300
ON FIRE BACKLIGHT SURFACES	Typ.	3300
	Max.	-

PIN ASSIGNMENT:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
VCC	VCI	GND	GND	CS	RS	WR	RD	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	DB8	DB9
19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
DB10	DB11	DB12	DB13	DB14	DB15	DB16	DB17	RESET	BWSJ	C86	NC	A	K	NC	NC	NC	NC

- NOTES:**
- 1. ○ : SPECIAL CHARACTERISTIC
 - 2. + : SAFETY CHARACTERISTIC
 - 3. ▽ : CRITICAL DIMENSION
 - 4. (.) : REFERENCE DIMENSION