

PIN	SYMBOL
1	NC
2	NC
3	NC
4	IM3
5	NC
6	RESET
7	VSYNC
8	HSYNC
9	DOTCLK
10	ENABLE
11	DB17
12	DB16
13	DB15
14	DB14
15	DB13
16	DB12
17	DB11
18	DB10
19	DB9
20	DB8
21	DB7
22	DB6
23	DB5
24	DB4
25	DB3
26	DB2
27	DB1
28	DB0
29	RD
30	WR
31	DC(RS)
32	CS
33	VSS
34	VDD
35	LED K
36	LED A



CIRCUIT DIAGRAM

Display type:TFT/Normal white
Display mode:Transmissive
interface: RGB/8080MCU 16/18 Bit
Viewing direction: 6'CLOCK(Good Veiwing Direction)
Driver IC: HX8347I
Logic volatage: 2.8±0.1V
Backlight: White LED(4-LED)
Vled=12.8±0.8V Iled=15mA
LCM BRIGHTNESS? 200 cd/M? (TYP)
Operating temprature: -20°C ~ +70°C
Storage temprature: -30°C ~ +80°C

**建议客户机壳开窗尺寸比LCD A.A单边大0.5mm，泡棉视窗小于LCD外形0.5mm