


Pin Description

Pin	Name	Pin	Name
1	VCOM	31	K
2	VDD	32	K
3	VDD	33	L/R
4	NC	34	U/D
5	RESET	35	VGL
6	STBYB	36	CABCEN1
7	GND	37	CABCEN0
8	RXIN0-	38	VGH
9	RXIN0+	39	A
10	GND	40	A
11	RXIN1-		
12	RXIN1+		
13	GND		
14	RXIN2-		
15	RXIN2+		
16	GND		
17	RXCLKIN-		
18	RXCLKIN+		
19	GND		
20	RXIN3-		
21	RXIN3+		
22	GND		
23	NC		
24	NC		
25	GND		
26	NC		
27	DIM0		
28	SELB		
29	AVDD		
30	GND		

- 1、Display type:TFT/Normal white
- 2、Display mode:Transmissive
- 3、The best View direction : 6 O'clock
- 4、Backlight: White LED(27-LED) / V=8.7~10.2 / I=180mA
- 5、LCM Luminance:300cd/m typ
- 6、Operating temprature: -10° C ~ +50° C
- 7、Storage temprature: -20° C ~ +60° C
- 8、建议泡棉视窗单边小于BZ VA 0.5mm
- 9、TOLERANCE: ±0.3mm
- 10、FPC CONNECTOR: FH12A-40S-0.5SH
- 11、ROHS REQUEST



Backlight LED Circuit