



NOTES:

1. Rating: 300V 10A
PITCH: 3.50mm
2. Insulation Withstands Voltage: AC 1500 V/MIN
3. Insulation Resistance: 500M Ω or more at DC500V
4. Using Temperature Range: -40°C~+105°C
5. Screw Torque Value: ~~2 kgf-cm~~ 1.5kgf-cm
6. Suitable Electric Wire: ~~30~16 AWG~~ 30~10 AWG
7. Undimensioned Tolerances:

-	∩	∇	0.05/10
⊥	//	≡	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONED TOLERANCES			±0.3

5	SOLDER PIN	0051B00100	P	BRONZE	Tin plated
4	COVER	0050C0XX00	1	PA66	GREEN
3	WIRE CAGE	X000002800	P	BRASS	M2/Ni Plated
2	SCREW	S000040000 S000008600	P	STEEL	M2/Zn Plated
1	HOUSING	0050A0XX00	1	PA66	GREEN

△	工程變更	WYG	05.05.13	ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
△	工程變更	WYG	04,12,06	DWG.	H ZH	DATE	01,06,25	UNITS	MM SHEET/OF 1/2
△	工程變更	YFY	03.12.14	CHK.		DATE		SCALE	6:1 (:) ⊕ ⊞
△	工程變更	YFY	03.10.24	APP.		DATE		NAME	EK350A-□□P
△	工程變更	PXQ	03.06.20						
REV.	CONTENT	CHK.	DATE	DINKLE ENTERPRISE CO.,LTD		DWG NO.	SP-02-EK350APO		