



NOTES:

1. Rating: 300V  $\frac{12A}{10A}$   $\triangle$   
PITCH: 3.81mm
2. Insulation Withstands Voltage:  
AC 2500V/MIN
3. Insulation Resistance:  
500M $\Omega$  or more at DC500V
4. Using Temperature Range:  
-40°C~+105°C
5. Screw Torque Value: 0.22~0.25N.M
6. Suitable Electric Wire: 30~16 AWG
7. Undimensioned Tolerances:

$\square$	$\triangle$	$\nabla$	0.05/10
$\perp$	$\parallel$	$\equiv$	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONS TOLERANCES			$\pm 0.3$

8. 表面處理為細噴沙

5	SOLDER PIN	0051B00100	P	BRONZE	Tin Plated
4	COVER	0051L1XX00	1	PA66	GREEN
3	WIRE CAGE	X000002800	P	BRASS	M2/Ni plated
2	SCREW	S000040000 <del>S000000000</del>	P	STEEL	M2/Zn plated
1	HOUSING	0051A1XX00	1	PA66	GREEN

$\triangle$	工程變更	WYG	05.05.13	ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
$\triangle$	產品更新	PXQ	03.06.20	DWG.	H ZH	DATE '01,07,03	UNITS	MM	SHEET/OF 1/2
$\triangle$	工程變更	DENG	03.01.01	CHK.		DATE	SCALE	6:1 ( : )	$\oplus$ $\square$
$\triangle$	工程變更	YFY	02.10.04	APP.		DATE			
$\triangle$	工程變更	HZH	02.5.13						
REV.	CONTENT	CHK.	DATE	<b>DINKLE</b>		<b>DINKLE</b>		NAME <b>EK381A-□□P</b>	
				<b>DINKLE ENTERPRISE CO.,LTD</b>		DWG NO.		SP-02-EK381APO	