



NOTES:

- 1. Rating: ~~150V 6A~~ 300V 12A
- PITCH: 3.81mm
- 2. Insulation Withstands Voltage: AC 1500V/MIN
- 3. Insulation Resistance: 500MΩ or more at DC500V
- 4. Using Temperature Range: -40°C~+105°C
- 5. Screw Torque Value: 2kgf-cm
- 6. Suitable Electric Wire: AWG ~~16~22~~ 16~30
- 7. Undimensioned Tolerances:

—	∩	∇	0.05/10
⊥	//	≡	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONS TOLERANCES			±0.3

8: 表面處理為細噴沙

6	WIRE CAGE	X000002800	P	BRASS	M2/Ni Plated
5	SCREW	<del>S000008600</del> S000040000	P	STEEL	M2/Zn Plated
4	SOLDER	0050B00200	P/2	COPPER	Tin Plated
3	SOLDER	0050B00100	P/2	COPPER	Tin Plated
2	HOUSING	0060A00000	1	PA66 PA66(V2)	GREEN
1	HOUSING	0051A00000	1	PA66 PA66(V2)	GREEN

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
⚠1	工程變更	JW	05.05.13	DWG.	林浚宏
⚠10	工程變更	WYG	05.04.15	CHK.	
⚠9	產品更新	YFY	03.06.26	APP.	
⚠8	工程變更	YFY	03.05.27		
REV.	CONTENT	CHK.	DATE	<b>DINKLE</b> ENTERPRISE CO.,LTD	
				NAME	EK381V4L-□□P
				DWG NO.	SP-02-EK381V4L