



NOTES:

1. Rating: 300V 20A (IEC 250V 10A)
Pitch: 5.08mm
2. Insulation Withstands Voltage:
AC 2000V/MIN
3. Insulation Resistance:
500M Ω or more at DC500V
4. Using Temperature Range:
-40°C~+105°C
5. Suitable Electric Wire:
24~12AWG(IEC 0.5~2.5mm²)
6. Torque Value: 4 kg-cm
7. Undimensioned Tolerances:

±	∇	□	0.05/10
∟	∟	≡	0.2/10
PITCH ERROR			0.05/10
DIMENSIONS			±0.3
TOLERANCES			±0.3

ITEM	NAME OF PART	NO. OF PART	QTY	MATERIAL	NOTES
6	SCREW	S0000003400	P	STEEL	M2.5/Zn Plated
5	WIRE CAGE	X000000800	P	STEEL	M2.5/Zn Plated
4	SOLDER POST	0052B00200	P/2	COPPER	Tin Plated
3	SOLDER POST	0052B00100	P/2	COPPER	Tin Plated
2	HOUSING	0063A1XX00	1	PA66	GREEN
1	HOUSING	0053A1XX00	1	PA66	GREEN

DWG:	林建宏	DATE	97.06.23	UNITS	MM	SHEET/OF	1/2
CHK:		DATE		SCALE	3:1		

REV.	3	增加凸筋	S W	06.08.22
CONTENT	工程變更	梁紅瑛	01.07.09	

DINKLE ENTERPRISE CO., LTD

NAME: **EK508V4L-□□P**

DWG NO: SP-02-EK508V4L