



- NOTES:
1. Rating: 300V 10A (IEC ~~250V 10A~~ 450V 24A) PITCH: 5.00mm
  2. Insulation Withstands Voltage: AC 1500V/MIN
  3. Insulation Resistance: 500MΩ or more at DC500V
  4. Using Temperature Range: -40°C~+105°C (IEC 0.5~2.5mm<sup>2</sup>)
  5. Suitable Electric Wire: 20~14AWG (IEC 1.5~2.5mm<sup>2</sup>)
  6. Undimensioned Tolerances:

—	∇	0.05/10
∟	∟	0.2/10
PICH ARRAY	≡	0.05/10
UNDIMENSIONS		±0.3
TOLERANCES		

△	工程變更	H J	06.06.14	△	1	HOUSING	0056ADXX00	P	PA66(V0)	DP882 M001
△	工程變更 (2005.04改裝)	HQH	06.01.06	△	2	CLAMP	0056B00300	P	STEEL	
△	工程變更	YJ	05.05.16		3	SOLDER PIN	0056B00200	P	COPPER	
△	工程變更 光之塵	梁紅英	01.01.11	APP.	4	END COVER	0056A4XX00	1	PA66(V0)	DP882 M001
△	工程變更	LHY	00.12.11		5	LEVER	0056A5XX00	P	POM	WHITE
△	CONTENT	CHK.	DATE							

ITEM	NAME OF PART	NO. OF PART	QTY	MATERIAL	NOTES
1	HOUSING	0056ADXX00	P	PA66(V0)	DP882 M001
2	CLAMP	0056B00300	P	STEEL	
3	SOLDER PIN	0056B00200	P	COPPER	
4	END COVER	0056A4XX00	1	PA66(V0)	DP882 M001
5	LEVER	0056A5XX00	P	POM	WHITE

**DINKLE**  
DINKLE ENTERPRISE CO., LTD  
DWG NO. SP-02-144RAP00